

#### **Product Description:**

The Viceroy is a unique lighting fixture that combines three lighting principles into one unit. It features a large reflector that creates a scoop effect, powered by a 400W LED engine with red, green, blue, amber, and lime colors. This setup produces a vast, soft-edged pool of light, ideal for general illumination and color blending.



Surrounding the scoop are eight segments containing 256 0.5W red, green, and blue LEDs. These segments can be controlled individually as pixels or through macros to create stunning circular color effects. Additionally, the fixture includes a five-segment center strobe bar equipped with high-power amber and cool white LEDs, which adds dynamic bursts of energy to any installation or production.

The Viceroy is housed in an IP65-rated enclosure, providing protection from inclement weather, making it suitable for both indoor and outdoor use. You can customize the unit with various grills and filter covers that soften the ring and strobe effects, or choose to frost the entire unit using its four-hole front-mounted screen system. Make the Viceroy a key part of your stage setup.

#### **400W RGBAL Center LED**

The Viceroy's 400W RGBAL engine delivers vibrant colors, smooth transitions, and high-quality white light, making it ideal for stage, architectural, and entertainment lighting.

#### Modern scoop 3-element effect

Delivers a broad, uniform, and powerful color wash. Ideal for architectural, entertainment, and club settings, it brings a modern, dynamic flair to any environment enhancing an immersive lighting experience.

Amber and Cool White 5-segment strobe bar

Featuring high-intensity strobe effects in Amber and Cool White, this 5-segmented bar creates dynamic, customizable patterns. Add the energy and impact you need to any performance or installation.

### **Outer 8-segment RGB Pixable ring**

This feature offers independent control over the RGB segments, allowing for versatile color effects around the fixture's perimeter. Perfect for creating clean, precise lighting accents in any setting.

### IP65 rating

With an IP65 rating, the Viceroy is protected against dust and rain, making it ideal for indoor and outdoor applications.

### **Mechanical Specifications**

IP Rating: IP65

Housing: Die-Cast Aluminum

Power Connection: Input: Seetronics SAC3MPX-67

Output: Seetronics SAC3FPX-67-01

Cable Input: Nema 5-15 to SAC3FX-67

(cable included)

Signal Connection: Input: Seetronics J5F2C-W-B-67 5-pin XLR

Output: Seetronics K5F2C-W-B-67 5-pin XLR

Fastening System: Mounting yoke with available quick-release

clamp accessory

LED Angle: Center: 55° / Bar: 60°

# **Electrical Specifications**

Light Source: Center: 1 X 400W Red, Green Blue, Amber, Lime

Ring: 256 X 0.5W Red, Green, Blue (8 segments)

Bar: 35 X 20W Amber, Cool White (5 Segments)

Color Temperature: 7105 K (all emitters)

CRI: 77 (all emitters full)

92 (configured)

Lumen Output: 13458 Lm

Power Supply: Electronic 100-240V AC 50/60

Power Consumption: 449 Watts 3.69 Amps @ 120V

# **Control System**

Control Protocols: DMX 512, RDM

RDM: Fixture Label, DMX Start Channel Address,

Channel Mode Set, Temperature Sensor,

Keep DMX Data, Scan Rate, Dimmer Curve,

White Balance RGBW, Fan Speed

Channel Modes: 4 Modes of operation


Mode 1: 5 Channel mode


Mode 2: 20 Channel mode


Mode 3: 39 Channel mode

Mode 4: 54 Channel mode

# Size and Weight







Fixture Size: 21.6" x 19" x 10.6"

(54.86 cm x 48.26 cm x 26.92 cm)

Fixture Weight: 42.1lbs (19.09 kg)

Packaged Size: 25.75" X 22.5" X 14.5"

(65.40 cm x 57.15 cm x 36.83 cm)

Packaged Weight: 53 lbs (24.04 kg)

### **Included Items**

Viceroy Power Cable Manual

### **Accessories**

Ring and Center Bar Diffusion 4155-ACC-H
Full Diffusion 4155-ACC-DIF
Hexagon Metal Grill 4155-ACC-HEX
Quick Release Clamp 4155-HOU-QUI
4 Unit Case CAS-4155-4-B

### **Customer Service**

MEGA-Lite has a customer support line to provide set-up help and answer any questions should you encounter a problem. Please visit our website for any other related technical documents. For service-related issues, please contact our service department at **service@mega.lighting** 

Operating Hours: Monday - Friday 9AM - 6PM CST Phone: (210) 684-2600 Sales@mega.lighting



18662 Bandera Rd Helotes, TX 78023 Phone (210)684-2600 / Fax (210)855-6279 www.mega.lighting / info@mega.lighting