



PIELITE™
MULTIBEAM



DESCRIPTION

The PieLite Multibeam is a versatile lighting fixture featuring 7 x 60W RGB + Cool White LED 4.5° pixel beams with individual control. It offers a rich color spectrum, clear white, and several mounting positions (horizontal, vertical, diagonal) that allow for creative designs. The modular grouping options (2, 3, or 4 units) allows for creative setups such as circles, semicircles, or standalone arrangements, making it ideal for corners or tight spaces.

The PieLite Multibeam's powerful, controllable beams can be used in various settings, enhancing any space with stunning visual effects.




Features




7 MOUNTING POSITIONS

The PieLite Multibeam offers 7 different mounting positions, including horizontal, vertical or diagonal, providing flexibility for various set up options.



MODULAR GROUPING 2, 3, 4 UNITS

Unleash your creativity by grouping 4 units to form a circle or 2 units to create a semicircle. Position it in corners, walls, ceilings or tight spaces to dazzle the room with powerful beams.



7 60W RGB + COOL WHITE 4.5° PIXEL BEAM

Achieve stunning white effects alongside a rich color spectrum, thanks to individual 4.5° pixel control for precise lighting customization.

Specifications.

Mechanical Specifications:

Housing:	Metal
Power connection:	Seetronics SAC3MPX Input & SACFPX output (Nema 5-15 to SAC3FX-67 cable included)
Signal connection:	3 and 5 Pin XLR in and out
LED angle:	4.5°
Segments:	7 Segments
Fastening System:	Quick release clamp mounts, multiple fixture quick release joining mounts

Control systems:

Control protocols:	DMX 512, RDM
RDM:	Fixture Label DMX start channel address Channel mode set
Channel modes:	4 Channel mode: Red, green, blue, white 10 Channel mode: Dimmer, R, G, B, W, strobe, shutter macro, shutter macro speed, color macro, color macro speed 28 Channel mode: Red, green, blue, white X 7 38 Channel mode: Dimmer, R, G, B, W, strobe, shutter macro, shutter macro speed, color macro, color macro speed
Display:	LCD

Electrical Specifications:

Light source:	7 X 60W RGBW
Color temperature:	7227K (white emitter only)
CRI (cool white):	73
Lumen output:	792
Power supply:	Electronic 90-264V AC 50/60
Power consumption:	537 Watts / 4.69 Amps @110V

Size and Weight:

Fixture size:	21" X 11.33" X 5.25" (53.34 cm X 28.77cm X 13.33 cm)
Fixture weight:	15 lb (6.8 kg) 14 oz
Packaged size:	25" X 13.75" X 8" (63.5 cm X 34.92 cm X 20.32 cm)
Packaged weight:	18 lb (8.1 kg)

MEGA **LITE**®
WWW.MEGA.LIGHTING

18662 Bandera Rd
Helotes, TX 78023

Phone (210)684-2600 / Fax (210)855-6279
info@mega.lighting

m e g a . l i g h t i n g