

Outerboot

WASH 340



Outerbot
WASH 340



DES CRIP TION

The Outerbot Wash 340 is equipped with three lighting elements. First is the pixel wash that can zoom creating a multi-color wash effect. The second element is a single point multibeam effect, and the third is an RGB Halo. Combining these elements creates a unique tool for your lighting arsenal. This unit is IP65-rated, making it suitable for any of your outdoor needs.



Features:



PIXEL WASH

The seven outer 40W RGBW LEDs allow for individual pixel control with 16-bit dimming and a 7°-33° zoom range. This fixture can create a slight beam or a smooth wash and it also features multiple wash presets for strobing, pixel control, and has 64 built-in macros.



SINGLE POINT MULTIBEAM EFFECT

Equipped with a center 60W RGBW LED that can produce a bright, powerful, and even projection. This fixture creates multi-colored beams of light that produce an explosion of colors in a Moonflower effect that transforms any room. This effect can be further enhanced using its bi-directional and speed-control prism.



RGB HALO

This unit offers an eye-candy Halo ring with 68 RGB SMD LEDs. It has a variety of hues and highly saturated colors with its 33-presets and an additional 17 macros, making this feature easy to control.



IP RATED

This unit is IP65-rated, adding a level of dust and water protection. This Ingress Protection rating certifies the unit suitable for multiple applications such as outdoor, wet, and/or dusty settings.

A stage light fixture is shown from a low angle, pointing upwards. The fixture has a central lens that emits a bright red beam of light. Four other lenses are positioned around the central one, each emitting a blue beam of light. The beams of light create a starburst pattern against the dark background. The fixture itself is black and has some controls visible at the bottom.

**Suitable for your
outdoor needs.**

Specifications.

Mechanical Specifications:

IP Rating:	IP65
Housing:	Die cast aluminum
Power connection:	Seetronics SACX3FX IP 65 Panel mount
Signal connection:	5 Pin XLR In and out & Artnet RJ45 in & out
Pan movement:	540° (16 Bit, 3 phase stepper motor)
Tilt movement:	220° (16 Bit, 3 phase stepper motor)
Zoom angle:	7° Beam angle to 33° Field angle (16 Bit)
Fuse:	Panel mount fuse (5x20mm T6.5A250V)
Fastening system:	Quick release clamp mount, bi directional

Electrical Specifications:

Power supply:	Electronic 100-240V AC 50/60
Power consumption:	2.86 Amps / 338 Watts @120V
Power link:	Max 6 units at 110V & 12 units at 220V

Outer LED:

Light source:	Seven 40W RGBW LEDs (16 Bit dimming)
Color temperature white:	8436K (White Emitter Only)
CRI (Warm white):	73
Segments:	7
Lumen output:	5654lm (Narrow) & 3546lm (Wide)

Center LED:

Light source:	60W RGBW LED
Color temperature white:	8380K
Single point multibeam prism:	Bi-directional, speed control

RGB Halo:

Light source:	68 RGB SMD LED
---------------	----------------

Control systems:

Control protocols:	DMX 512, Artnet, SACN
RDM:	Yes
Channel modes:	6 Modes of operation Mode 1: 25 Channel mode Mode 2: 27 Channel mode Mode 3: 30 Channel mode Mode 4: 31 Channel mode Mode 5: 37 Channel mode Mode 6: 52 Channel mode
Display:	Auto Flip display

Size and Weight:

Fixture size:	16.5" X 14.5" X 19.12" (41.91 cm X 36.83 cm X 48.56cm)
Fixture weight:	56 lb (25.40 kg)
Packaged size:	21" X 18.5" X 23.5" (53.34 cm X 46.99 cm X 59.69cm)
Packaged weight:	57.5 lb (26.08 kg)

MEGALITE®
WWW.MEGA.LIGHTING

18662 Bandera Rd
Helotes, TX 78023

Phone (210)684-2600 / Fax (210)855-6279
info@mega.lighting

m e g a . l i g h t i n g